

SKU : **Sparkle GTX285 2048MB PCI-Express 3-way SLI support Video Card**
 Model Number : **SXX2852048D3-VP**
 UPC Code : **4710710446086**

Key Messages

- 2048MB High Capacity Memory
- 3 way SLI Support
- Microsoft DirectX 10 support
- 55nm chip for lower power consumption
- SLI Multi-Monitor support
- **Powerful Cooling System**



Specifications

GPU	GTX 285
Core Clock	648 MHz
Memory Type	2048MB GDDR3
Memory Clock	2322 MHz
Memory Interface	512-Bit
Shader Clock	1476 MHz
Bus Type	PCI-Express 2.0
Output	Dual-link DVI-I x 2
HDPC	Yes
OpenGL	2.1
DirectX	DX10 Shader Model 4.0

Minimum system requirement

- Minimum 550W or greater system power supply (with a minimum 12V current rating of 40A) with two 6-pin PCI Express supplementary power connectors

Accessories

- Sparkle CD Driver
- Sparkle manual
- DVI adapter
- Power cable * 2

Key Features

PhysX™ by NVIDIA GeForce GPU support for NVIDIA PhysX technology enabling a totally new class of physical gaming interaction for a more dynamic and realistic experience with GeForce



CUDA technology unlocks the power of the GPU's processor cores to accelerate the most demanding system tasks-such as video transcoding-delivering incredible performance over traditional CPUs



The combination of high-definition video decode acceleration and post-processing that delivers unprecedented picture clarity, smooth video, accurate color, and precise image scaling for movies and video.



Industry leading 3-way NVIDIA SLI technology offers amazing performance scaling by implementing AFR(Alternate Frame Rendering), under Windows Vista with solid, state-of-the-art drivers.



Card / Box / Carton information

Weight (LBs)	2.60 lbs
Box type	Large
Qty per carton	10 pcs
Carton dimension	17.4" x 13.6" x 13.3"
Box dimension	12" x 8.3" x 2.5"